

# DELTA TRAILCUTTER AT4S

## ALL-TERRAIN SUV/LT

The Delta Trailcutter AT4S is designed to deliver all-weather superior traction for SUVs, pickups and vans, both on and off the road. The Delta Trailcutter AT4S provides exceptional handling, while maintaining a quiet and comfortable ride, making it the perfect choice to tackle whatever obstacles the elements throw at your vehicle! The Delta Trailcutter AT4S is designated with the USTMA Three Peak Mountain Snow Flake (3PMSF) symbol, indicating superior performance in snow and winter conditions.

## FEATURES & BENEFITS

- Certified with USTMA 3PMSF symbol for severe winter performance
- Aggressive open shoulder tread design expels water, winter slush and mud for optimum traction in all terrain conditions
- Extra-deep tread sipes at varying angles improve comfort without sacrificing traction
- Jagged edge tread blocks improve grip on ice and in the mud providing superior traction
- Zigzag grooves and continuous center block provide outstanding grip and superior handling

## SIZES

- More than 40 popular Metric and LT sizes covering 15", 16", 17", 18" and 20" diameters

## FITS

- Mid/Full-size pickups, Jeeps, SUVs and vans



## PERFORMANCE



# DELTA TRAILCUTTER AT4S ALL-TERRAIN SUV/LT

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS@PSI	DUAL MAX. LOAD LBS@PSI	SHIP WEIGHT (LBS.)
DTC64	235/75R15	109T	XL	660 A B	12	RBL	6.0	9.06	28.86	2271 @ 50	-	36
DTC79	245/75R16	111T	SL	660 A B	12	RBL	6.5	9.76	30.47	2403 @ 51	-	39
DTC81	265/75R16	116T	SL	660 A B	13	RBL	7.0	10.55	31.65	2756 @ 51	-	45
DTC53	235/70R16	106T	SL	660 A B	12	RBL	6.0	9.37	28.98	2094 @ 51	-	35
DTC80	245/70R16	107T	SL	660 A B	12	RBL	6.5	9.76	29.53	2149 @ 51	-	38
TRC86*	255/70R16	111T	SL	660 A B	12	RBL	6.5	10.24	30.08	2403 @ 51	-	41
DTC93	265/70R16	112T	SL	660 A B	13	RBL	7.0	10.79	30.63	2469 @ 51	-	43
TRC45*	235/75R17	109T	SL	660 A B	12	RBL	6.0	9.06	30.87	2271 @ 51	-	39
TRC44*	235/70R17	108T	XL	660 A B	12	RBL	6.0	9.37	30.00	2205 @ 50	-	38
DTC89	245/70R17	110T	SL	660 A B	12	RBL	6.5	9.76	30.55	2337 @ 51	-	41
DTC10	255/70R17	112T	SL	660 A B	12	RBL	6.5	10.24	31.10	2469 @ 51	-	43
DTC87	265/70R17	115T	SL	660 A B	13	RBL	7.0	10.79	31.65	2679 @ 51	-	48
DTC51	245/65R17	107T	SL	660 A B	12	RBL	7.0	9.69	29.53	2149 @ 51	-	39
TRC20*	255/65R17	110T	SL	660 A B	12	RBL	7.0	10.31	30.08	2337 @ 51	-	42
DTC58	265/65R17	112T	SL	660 A B	12	RBL	7.5	10.59	30.55	2469 @ 51	-	42
DTC52	255/70R18	113T	SL	660 A B	12	RBL	6.5	10.24	32.09	2535 @ 51	-	45
DTC22	265/70R18	116T	SL	660 A B	13	RBL	7.0	10.79	32.64	2756 @ 51	-	47
DTC56	265/65R18	114T	SL	660 A B	12	RBL	7.5	10.59	31.54	2601 @ 51	-	45
DTC41	275/65R18	116T	SL	660 A B	13	RBL	7.5	10.87	32.09	2756 @ 51	-	49
DTC91	265/60R18	110T	SL	660 A B	12	RBL	7.5	10.51	30.55	2337 @ 51	-	45
DTC15	275/60R20	115T	SL	660 A B	12	RBL	7.5	10.79	33.07	2679 @ 51	-	50
DTC48	275/55R20	117T	XL	660 A B	12	RBL	7.5	10.98	31.93	2833 @ 50	-	48
DTC17	LT235/85R16	120/116R	E	-	16	RBL	6.0	9.09	31.73	3042 @ 80	2778 @ 80	47
DTC26	LT225/75R16	115/112R	E	-	16	RBL	6.0	8.46	29.29	2680 @ 80	2470 @ 80	41
DTC38	LT245/75R16	120/116R	E	-	16	RBL	6.5	9.53	30.47	3042 @ 80	2778 @ 80	47
DTC39	LT265/75R16	123/120R	E	-	17	RBL	7.0	10.35	31.65	3415 @ 80	3085 @ 80	52
DTC67	LT285/75R16	126/123R	E	-	18	RBL	7.5	11.14	32.83	3750 @ 80	3415 @ 80	61
DTC95	LT235/80R17	120/117R	E	-	16	RBL	6.0	9.09	31.81	3085 @ 80	2835 @ 80	49
DTC19	LT245/75R17	121/118R	E	-	16	RBL	6.5	9.53	31.69	3195 @ 80	2910 @ 80	48
DTC70	LT245/70R17	119/116S	E	-	16	RBL	6.5	9.76	30.71	3000 @ 80	2755 @ 80	48
DTC92	LT265/70R17	121/118S	E	-	17	RBL	7.0	10.75	31.89	3195 @ 80	2910 @ 80	54
DTC84	LT285/70R17	121/118S	E	-	18	RBL	7.5	11.57	32.99	3195 @ 80	2910 @ 80	59
TRC02*	LT315/70R17	121/118S	E	-	19	RBL	8.0	12.72	34.65	3195 @ 65	2910 @ 65	74
DTC30	LT265/70R18	124/121S	E	-	17	RBL	7.0	10.75	32.87	3525 @ 80	3195 @ 80	59
DTC72	LT275/70R18	125/122S	E	-	18	RBL	7.0	11.02	33.43	3640 @ 80	3305 @ 80	62
DTC40	LT275/65R18	123/120S	E	-	18	RBL	7.5	10.75	32.09	3415 @ 80	3085 @ 80	58
TRC57*	LT285/65R18	125/122S	E	-	18	RBL	8.0	11.30	32.56	3640 @ 80	3305 @ 80	62
TRC36*	LT325/65R18	127/124R	E	-	19	RBL	9.0	13.03	34.61	3860 @ 65	3525 @ 65	76
DTC43	LT275/65R20	126/123S	E	-	18	RBL	7.5	10.79	34.09	3750 @ 80	3415 @ 80	62
TRC74*	LT265/60R20	121/118R	E	-	17	RBL	7.5	10.55	32.52	3195 @ 80	2910 @ 80	56
TRC37*	LT285/60R20	125/122R	E	-	18	RBL	8.0	11.34	33.46	3640 @ 80	3305 @ 80	62
TRC35*	LT325/60R20	121/118S	D	-	19	RBL	9.0	12.80	35.35	3195 @ 50	2910 @ 50	77
TRC34*	LT285/55R20	122/119R	E	-	18	RBL	8.0	11.22	32.36	3305 @ 80	3000 @ 80	60
TRC54*	LT305/55R20	121/118S	E	-	18	RBL	8.5	12.28	33.23	3195 @ 65	2910 @ 65	68
DTC46	31X10.50R15LT	109R	C	-	17	RBL	7.0	10.39	30.51	2270 @ 50	-	46
TRC71*	35X12.50R20LT	121Q	E	-	19	RBL	8.5	12.48	34.61	3195 @ 65	-	74

\*Branded Trailcutter AT4S, same tread pattern.